



TURN SIX AT RIVERSIDE

**SHELBY
MUSTANG
GT 350**

American. SCCA Class B production sports car champion in 1965 and 1966. Body style: two-door fastback. Engine: Ford overhead valve V8. Bore and stroke: 4" x 2.87". Displacement: 289 cu. in. Compression ratio: 10.5 to 1. Brake horsepower: 306 @ 6000 rpm. Torque: 329 lbs.-ft. @ 4200 rpm. Induction and exhaust: special free-breathing Shelby design. Transmission: 4-speed synchromesh. Suspension: independent coil spring, front; semielliptic leaf spring, rear. Shelby-modified for 30% less cornering roll. Brakes: disc, front; air-cooled drum, rear. Steering ratio: 16 to 1. Wheelbase: 108". Overall length: 186.6". Weight: 2723 lbs.

Autolite
speaks a
performance
language all
its own

And that language is Ford *total* performance. Total performance knowledge requires participation in every phase of racing. So everywhere racing goes—Ford, and only Ford goes. To Indy, Le Mans, Darlington, Riverside, Daytona, drag strips. And where Ford goes . . . Autolite goes. Designing, building, and testing new performance techniques. For

Indy cars. For dragsters. For stockers. For your car, too. Racing is the only road to high-performance know-how. And only Autolite has traveled every inch of it.

AUTOLITE

...the spark behind the total performance company...

